

Technical Specification/ Product Datasheet

Clark-Drain Ltd., Station Road, Yaxley, Peterborough, PE7 3EQ. England.



CD 128 KMC (pictured)

CD 129 KMC CD 130 KMC

Product Group: Ductile Iron Kitemark Gully Grates & Frames

Sub-Category: C250 Hinged Gully Grates & Frames for use in kerbside areas

Material Grade/s: Spheroid Graphite Iron Grade EN-GJS-500-7 to BS EN 1563:2011

Temporary Bitumen-based paint coating to BS 3416:1991

Basic Dimensions (mm):		CD 127 KMC	: CD 128 KMC :	CD 129 KMC :	CD 130 KMC
	Clear Opening:	440 x 335	336 x 308	336 x 308	440 x 335
	Overall Size:	530 x 495	480 x 393	482 x 395	535 x 500
	Depth:	75	75	100	100
Weight (kgs):		29	14	19	33
Frame Pressure Bearing Area (N/mm²):		4.28	6.45	5.80	4.28
Waterway Area (cm²):		866	685	686	866

Load Rating Classification: C250 (25 tonnes)

Features:

- BSI Kitemark Certified to BS EN124:1994 (copy certificate available upon request)

- 3-sided flange for installation against kerbs

- Theft-deterrent captive hinge

Date Issued: 24/12/15

