ACO Inform



Maintaining the flow of information

PRODUCT, SUPPLY AND SERVICE INFORMATION

New ACO EasyLine H50 Channel Drain

ACO is proud to announce the launch of the ACO Easyline channel system tailored for low-profile installations.

ACO Easyline is ideal for installations requiring a low profile and draining a smaller surface area, for example balconies, terraces, facades and thresholds.

The lightweight plastic channel eases installation, along with its inbuilt 90-degree corner option. The range of accessories allow for rainwater to be drained from the end, sides or underneath of the channel.

ACO Easyline is available in a black channel and matching grating or with a galvanised steel grating and is the ideal choice for domestic use, adding both function and style to your outdoor space.

ACO Easyline's low profile enables installation where depth is at a premium, but care should be taken to check the channel can adequately drain the paved surface.*

Features include:

- Ideal for domestic installations where a low profile channel is required such as balconies, facades and thresholds
- Quick and easy to install, including interlocking joints between channels for straight-run and right-angle installation
- Full range of accessories to facilitate end, side and underneath connection to surface water drainage
- Fully certified to Load Class A 15 BS EN 1433:2002





Technical Specification

Product Code	Description	Length [mm]	Width [mm]	Invert [mm]	Weight [kg]	Pack Quantity
330008	Easyline H50 black channel assembly c/w galanvised steel grating 1000mm A 15	1000	125	50	1.61	198
330020	Easyline H50 accessory kit black (vertical outlet adapter Ø110, 2 end-caps Ø32 outlet, closed end cap)					10

ACO Water Management

A division of ACO Technologies plc ACO Business Park, Hitchin Road, Shefford, Bedfordshire SG17 5TE

Tel: 01462 816666

Sales: customersupport@aco.co.uk Project pricing: awmprojects@aco.co.uk Technical: technical@aco.co.uk

www.aco.co.uk

^{*} A 5m run of Easyline A50 channel with a single outlet will drain up to 35m² paved area during a 50mm per hour rainfall event (in accordance with the guidance in Building Regulations for England 2015 Section H3 2.4).